

11-01-00

Docket No: NFCS-00-016

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application of:

Huang, et al.

Serial No. [Not yet assigned; this application is
a divisional of co-pending application
SN 09/365,680, filed August 2, 1999

Filed: October 30, 2000

For: OPTICAL POLARIZATION BEAM
COMBINER/SPLITTER

) Art Unit:

) Examiner:

CERTIFICATE OF MAILING

"Express Mail" mailing label no: EK175755008US

Date of Deposit: October 30, 2000

I hereby certify that this correspondence is being
deposited with the United States Postal Service "Express
Mail Post Office to Addressee" service under 37 CFR
1.10 on the date indicated above and is addressed to:

Box Patent Application
Assistant Commissioner for Patents
Washington, D.C. 20231

On: 10/30/00
Date

Teri Muir
Teri Muir

DIVISIONAL APPLICATION TRANSMITTAL LETTER

37 C.F.R. § 1.53(b)

Honorable Assistant Commissioner
for Patents

Box Patent Application
Washington, D.C. 20231

Dear Sir:

This is a request for filing under the Continuing Application Procedure, 37 C.F.R.
§ 1.53.(b) for a divisional application of prior application Serial No. 09/365,680, filed
August 2, 1999, naming inventors Yonglin Huang and Ping Xie. The prior application is
assigned of record to New Focus, Inc. Enclosed for filing are 21 pages specification, 9

In Re Application of: Huang, et al.

Serial No. <not yet assigned>

Filed: 10/30/00

For: OPTICAL POLARIZATION BEAM
COMBINER/SPLITTER

Art Unit:

Examiner:

I hereby certify that this correspondence is being deposited with the United States Postal Service with sufficient postage as First Class Mail, in an envelope addressed to:

Assistant Commissioner for Patents
Washington, D.C. 20231

10-30-00

Date _____

Seri Muri
Signature

Signature

TERI MUIR

Print Name

PRELIMINARY AMENDMENT

Honorable Assistant Commissioner of Patents

Washington, D.C. 20231

Dear Sir:

Kindly amend the above identified application as follows:

IN THE SPECIFICATION:

At Page 1, Line 10, after the Title of the Invention, please insert:

This application is a Divisional Application of Ser. No. 09/365,680, filed August 1, 1999.

IN THE CLAIMS:

Kindly cancel claims 1, 7-21.

REMARKS

Early consideration of the application in view of the above amendments and the following remarks is requested.

Applicants elect to pursue claims 2-6 in the present application

No additional fee is due.

On the basis of the above amendments and remarks, early consideration of this application and early allowance are respectfully requested.

Respectfully,

By: MB

Timothy A. Brisson
Attorney for Applicant
Reg. No. 44,046

Telephone: (775) 586-9500
Facsimile: (775) 586-9550

[illegible]

This application is submitted in the names of inventors Yonglin Huang and Ping Xie, assignors to New Focus, Inc., a California Corporation.

5

SPECIFICATION

OPTICAL POLARIZATION BEAM COMBINER/SPLITTER

10

BACKGROUND OF THE INVENTION

1. Field of the Invention

2. The Prior Art

Optical polarization beam splitter/combiners are known in the art. These devices may be used in optical communication in many ways including, but not limited to, optical power multipliers for combining two optical pump beams to increase optical pumping power, in coherent optical communications applications, and as optical polarization division multiplexers.

20

Two examples of prior art optical polarization beam splitter/combiners are shown in FIGS. 1A and 1B and FIGS. 2A and 2B, respectively. In the optical polarization beam splitter of FIG. 1A, an input beam enters from the fiber located at the left side of the

figure. For the beam splitting operation, the incoming beam from fiber 1 at the left is collimated by the lens 1, and then enters the optical polarization beam splitter cube. The optical polarization beam splitter cube is able to split an arbitrary polarized light into two separated beams with orthogonally polarized directions. A first beam exits to the right and is coupled to fiber 2 through lens 2. A second beam exits in an upward direction and is coupled to fiber 3 through lens 3. In this way, an optical polarization beam splitter is realized. These three fibers could each be a single mode fiber, a polarization maintaining (PM) fiber, or even a multi-mode fiber.

The prior-art device depicted in FIG. 1A may be used as a bi-directional device if fiber 2 and fiber 3 are PM fibers, such that the optical beam polarization states coming from these two fibers are well defined and orthogonal to each other. Then these two beams can be added together at fiber 1 as shown in FIG. 1B. In this way, an optical polarization beam combiner is realized.

The device depicted in FIGS. 1A and 1B functions for its intended purpose. It however, suffers from several disadvantages, such as a larger device size necessitated by

the need to employ an orthogonally disposed beam, suffer from a low extinction ratio, difficult to manage the fibers.

A second prior-art embodiment of an optical polarization beam combiner/splitter is depicted in FIGS. 2A and 2B. The optical principles of operation of the embodiment of FIGS. 2A and 2B are almost the same as those of FIGS. 1A and 1B.

Referring to FIG. 2A, a birefringent crystal is used to split the incoming arbitrary polarization light focussed from fiber 1 by lens 1 into two parallel beams having orthogonal polarization directions. These two beams are focused into fiber 2 and fiber 3, respectively, by lenses 2 and 3, such that the optical polarization beam splitter is realized. As shown in FIG. 2B, an optical polarization beam combiner can be realized as well. Compared to the embodiments of FIGS. 1A and 1B, the approach of FIGS. 2A and 2B provides high extinction ratio, employs fewer optical parts, and could be manufactured without the use of an optical epoxy in the optical path.

The device depicted in FIGS. 2A and 2B has its own drawbacks. Since fiber 2 and fiber 3 are located at the same side of the device, the birefringent crystal must have a

length sufficient separate the two beams enough to accommodate the required spacing between lenses 2 and 3. Typically, lenses for this application have diameters of around 1.8mm, requiring the minimum spacing between lens axes to also be about 1.8mm. A birefringent must have a length of about 18mm to provide the required beam separation of at least about 1.8mm to accommodate the placement of lenses 2 and 3.

BRIEF DESCRIPTION OF THE INVENTION

An optical polarization beam splitter according to one embodiment of the present invention comprises a first optical fiber having an end defining a first optical axis, a second optical fiber having an end defining a second optical axis, and a third optical fiber having an end defining a third optical axis parallel to and spaced apart from the second optical axis. A collimating lens is disposed along the first optical axis positioned to form a collimated optical beam from the first optical fiber. A focussing lens is disposed along a path of the collimated optical beam. A birefringent walk-off crystal has a first face adjacent to the focussing lens and a second face located at a focal plane of the focussing lens and in contact with the ends of the second and third optical fibers. The birefringent crystal is oriented such that and has a thickness between its first and second faces selected such that a first component of the optical beam having a first polarization exits

the crystal at its second face and enters the end of the second optical fiber along the second optical axis and a second component of the optical beam having a second polarization orthogonal to the polarization of the first polarization exits the crystal at its second face and enters the end of the third optical fiber along the third optical axis.

5

An optical polarization beam splitter according to another embodiment of the present invention comprises a first optical fiber having an end defining a first optical axis, a second optical fiber having an end defining a second optical axis, and a third optical fiber having an end defining a third optical axis parallel to and spaced apart from the second optical axis. A collimating lens is disposed along the first optical axis and is positioned to form a collimated optical beam from the first optical fiber. A birefringent walk-off crystal is disposed in a path of the collimated optical beam. The crystal is oriented such that and has a thickness between first and second faces thereof selected such that a first component of the optical beam having a first polarization transits the crystal along a first path and a second component of the optical beam having a second polarization orthogonal to that of the first polarization transits the crystal along a second path disposed at a walkoff angle with respect to the first path. The first and second paths exit the second face of the crystal as substantially parallel first and second paths. A

Wollaston prism (a pair of wedges) is disposed along the substantially parallel first and second paths and oriented such as to bend the substantially parallel first and second paths towards each other to form converging first and second paths. A focussing lens is disposed along the converging first and second paths and positioned such that a first component optical beam travelling along the first converging path is directed into the end of the second optical fiber along the second optical axis and a second component optical beam travelling along the second converging path is directed into the end of the third optical fiber along the third optical axis.

An optical polarization beam splitter according to another embodiment of the present invention comprises a first optical fiber having an end defining a first optical axis, a second optical fiber having an end defining a second optical axis, and a third optical fiber having an end defining a third optical axis parallel to and spaced apart from the second optical axis. A collimating lens is disposed along the first optical axis and is positioned to form a collimated optical beam from the first optical fiber. A first Wollaston prism is disposed in a path of the collimated optical beam and oriented such that a first component of the optical beam having a first polarization transits the prism along a first path disposed at a first angle with respect to the first optical axis and a

second component of the optical beam having a second polarization orthogonal to that of the first polarization transits the prism along a second path disposed at a second angle with respect to the first optical axis, the first and second angles being substantially symmetrical about the first optical axis. A second Wollaston prism is disposed along the first and second paths and oriented such as to bend the first and second paths towards each other to form converging first and second paths. A focussing lens is disposed along the converging first and second paths and positioned such that a first component optical beam travelling along the first converging path is directed into the end of the second optical fiber along the second optical axis and a second component optical beam travelling along the second converging path is directed into the end of the third optical fiber along the third optical axis.

An optical polarization beam splitter according to another embodiment of the present invention comprises a first optical fiber having an end defining a first optical axis, a second optical fiber having an end defining a second optical axis, and a third optical fiber having an end defining a third optical axis parallel to and spaced apart from the second optical axis. The second and third optical axes are symmetrical about the first optical axis. A first focussing lens is disposed along the first optical axis. A Wollaston

prism is disposed at a location along the first optical axis where a focal point of the first focussing lens lies on an interface between two component pieces of the prism wedge such that a first component of an optical beam from the first optical fiber having a first polarization is directed along a first path disposed at a first angle with respect to the first optical axis and a second component of the optical beam having a second polarization orthogonal to that of the first polarization is directed along a second path disposed at a second angle with respect to the first optical axis, the first and second angles being substantially symmetrical about the first optical axis. A second focussing lens is disposed along the first and second paths at a location selected to focus a first component optical beam into the end of the second optical fiber to focus a second component optical beam into the end of the third optical fiber.

BRIEF DESCRIPTION OF THE DRAWING FIGURES

FIGS. 1A and 1B are optical block diagrams of a first typical prior-art device useful as both a beam combiner and beam splitter.

FIGS. 2A and 2B are optical block diagrams of a second typical prior-art beam useful as both a beam combiner and beam splitter.

FIG. 3 is an optical block diagram of an optical polarization beam combiner/splitter in accordance with a first embodiment of the invention.

5 FIG. 4 is an optical block diagram of an optical polarization beam combiner/splitter in accordance with a second embodiment of the invention.

FIG. 5 is an optical block diagram of an optical polarization beam combiner/splitter in accordance with a third embodiment of the invention.

10 FIG. 6 is an optical block diagram of an optical polarization beam combiner/splitter in accordance with a fourth embodiment of the invention.

DETAILED DESCRIPTION OF A PREFERRED EMBODIMENT

15 Persons of ordinary skill in the art will realize that the following description of the present invention is illustrative only and not in any way limiting. Other embodiments of the invention will readily suggest themselves to such skilled persons having the benefit of this disclosure.

Referring now to FIG. 3, an optical block diagram of an embodiment of an optical polarized beam combiner/splitter 10 according to the present invention is shown. A first fiber ferrule 12 terminates fiber 14 at an angled face 16 thereof. Angled face 16 may be polished to an angle of about 8° to 10° as is the end of fiber 14, as is known in the art to avoid deleterious effects from internal reflections in the optical fiber. Fiber 14 carries a combined optical beam having a first component polarized in a first direction and a second optical beam polarized in a second direction orthogonal to the first direction. Fiber ferrule 12 may have a length in the optical path direction of about 4 mm.

A first lens 18 may be spaced apart from fiber ferrule 12 by about 1mm, may have a length in the optical path direction of about 3 mm and collimates the combined beam 20 emerging from the end of fiber 14 to produce a collimated combined beam 22. A second lens 24 may be spaced apart from first lens 18 by a distance of about 2mm, may have a length in the optical path direction of about 3 mm and focuses the collimated combined beam 22 at a focal point 26 on a first face of birefringent walkoff crystal 28. As presently preferred, both lens 18 and lens 24 may be graduated-index-of-refraction (GRIN) lenses, although conventional lenses may also be employed. Persons of ordinary skill in the art

will appreciate that two separate lenses 18 and 24 are employed to perform the collimating and focussing functions to minimize the introduction of spherical aberrations.

Birefringent walkoff crystal 28 is disposed at an angled face 30 of a ferrule 32. A first component beam 34 from fiber 14 passes through birefringent walk-off crystal 28 without refraction and a second component beam 36 passes through birefringent walk-off crystal 28 after being refracted at an downward angle. The thickness of birefringent walk-off crystal 28 is selected so that the paths of beams 34 and 36 walk off from one another by a distance selected to match the spacing between optical fibers 38 and 40 held in ferrule 32. Birefringent walk-off crystal 28 may be comprised of a material such as YVO_4 , LiNbO_3 , etc. Typical thicknesses for birefringent walk-off crystal 28 are in the range of from about 1mm to about 2mm and the distance between second lens 24 and ferrule 32 may be between about 1mm to 2mm. As those of ordinary skill in the art will appreciate, changing the incident angle of the birefringent walk-off crystal 28 will change the walk-off distance.

From an examination of FIG. 3 persons of ordinary skill in the art will appreciate that an improved optical polarizing beam combiner/splitter has been described. Because

the optical paths in optical polarizing beam combiner/splitter 10 are all substantially parallel to a single optical axis, it can be packaged in a small, compact coaxial package, thus allowing for a smaller footprint and providing an improved ease in fiber management. Furthermore, the combination of optical components utilized in the embodiment of FIG. 3 permits close spacing of the two parallel-axis component beams and avoids the use of longer walk-off distances that would otherwise be required to provide sufficient beam spacing to accommodate the physical sizes of the optical components. For example, by using the optical components of the present invention, the two parallel axis component beams may be spaced apart by as little as 0.125mm (125 microns). In addition, the entire length of the splitter/combiner in the illustrative embodiment of FIG. 3 is less than about 18mm to about 20mm.

Persons of ordinary skill in the art will appreciate that the device of FIG. 3 has been described by following the optical path from left to right across the figure and performs the function of a beam splitter. Such skilled persons will appreciate that two oppositely polarized optical beams emerging from fibers 38 and 40 on the right and travelling in the direction from right to left across the drawing figure will be combined

and directed into fiber 14 at the left of FIG. 3 in accordance with the principles of the present invention, so long as optical fibers 38 and 40 are PM fibers.

Referring now to FIG. 4, an optical block diagram of another embodiment of an optical polarized beam combiner/splitter 40 according to the present invention is shown.

The embodiment of FIG. 4 has been described for an orientation wherein a coincident beam having two components enters from optical fiber 42 at the left of the figure and is split into two component beams which emerge at the right side of the figure, but persons of ordinary skill in the art will appreciate that the analysis of two component beams entering the combiner/splitter from the right and being combined and directed into optical fiber 42 according to the present invention follows from the same optical principles described as responsible for beam splitting, so long as the optical fibers delivering the two component beams are polarization maintaining fibers.

Optical fiber 42 is disposed in ferrule 44 as is known in the art and is end polished at an angle as is known in the art. Diverging composite optical beam 46 from the end of optical fiber 42 is collimated by collimating lens 48 and collimated composite optical

beam 50 enters birefringent walkoff crystal 52. A first optical beam component transits crystal 52 on beam path 54 and a second optical beam component transits crystal 52 on beam path 56 at a walkoff angle with respect to beam path 54. The length of birefringent crystal 52 is selected to provide a selected walkoff distance indicated by double-headed arrow 58 between the two component optical beams. In the illustrative embodiment of FIG. 4, the ferrule 44 may have a length of about 4mm, the collimating lens 48 may be spaced from ferrule 44 by about 0.1mm, and may have a length in the optical path direction of about 5mm. The birefringent crystal 52 may have a length of about 10mm, and may be spaced from collimating lens 48 by about 0.2mm.

A Wollaston prism 60 is disposed in the paths of optical beams 54 and 56 to bend the propagation directions of optical beams 54 and 56 so that they may be focussed by lens 62 such that they enter optical fibers 64 and 66, respectively, disposed in ferrule 68. As presently preferred, lens 62 comprises a GRIN lens, although a conventional lens may also be employed. In the illustrative embodiment of FIG. 4, the Wollaston prism 60 may have a length of about 4mm, and may be spaced from birefringent crystal 52 by about 0.2mm. Lens 62 may have a length of about 5mm, and may be spaced from Wollaston prism 60 by about 0.2mm. Ferrule 68 may have a length of about 4mm, and may be

spaced from lens 62 by about 0.1mm. The entire length of the splitter/combiner in the illustrative embodiment of FIG. 4 is less than about 30mm to about 40mm.

Referring now to FIG. 5, an optical block diagram of another embodiment of an optical polarized beam combiner/splitter 70 according to the present invention is shown.

As with the other embodiments disclosed herein, the embodiment of FIG. 5 has been described for an orientation wherein a coincident beam having two components enters from optical fiber 72 at the left of the figure and is split into two component beams which emerge at the right side of the figure, but persons of ordinary skill in the art will appreciate that the analysis of two component beams entering the combiner/splitter from the right and being combined and directed into optical fiber 72 according to the present invention follows from the same optical principles described as responsible for beam splitting, so long as the optical fibers delivering the two component beams are polarization maintaining fibers.

Optical fiber 72 is disposed in ferrule 74 as is known in the art and is end polished at an angle as is known in the art. Diverging composite optical beam 76 from the end of

optical fiber 72 is collimated by collimating lens 78. Ferrule 74 may have a length of about 4mm, and may be spaced from collimating lens 78 by about 0.1mm. Collimated composite optical beam 80 enters first Wollaston prism 82. A first optical beam component transits prism 82 on beam path 84 and a second optical beam component transits crystal 82 on beam path 86. Beam paths 84 and 86 are substantially symmetrical about the optical axis of the first beam path 76 out of first fiber 72. First Wollaston prism 82 may have a length of about 2mm, and may be spaced from collimating lens 78 by about 0.3mm.

A second Wollaston prism 88 is disposed in the paths of optical beams 84 and 86 to bend the propagation directions of optical beams 84 and 86 towards each other so that they may be focussed by lens 90 such that they enter optical fibers 92 and 94, respectively, disposed in ferrule 96. As presently preferred, lens 90 comprises a GRIN lens, although a conventional lens may also be employed. Second Wollaston prism 88 may have a length of about 2mm, and may be spaced from first Wollaston prism 82 by about 4mm. Lens 90 may have a length of about 5mm, and may be spaced from second Wollaston prism 88 by about 0.3mm. Ferrule 96 may have a length of about 4mm, and may be spaced from lens 90 by about 0.1mm.

Referring now to FIG. 6, an optical block diagram of another embodiment of an optical polarized beam combiner/splitter 100 according to the present invention is shown.

5 As with the other embodiments disclosed herein, the embodiment of FIG. 6 has been described for an orientation wherein a coincident beam having two components enters from optical fiber 102 at the left of the figure and is split into two component beams which emerge at the right side of the figure, but persons of ordinary skill in the art will appreciate that the analysis of two component beams entering the combiner/splitter from the right and being combined and directed into optical fiber 102 according to the present invention follows from the same optical principles described as responsible for beam splitting, so long as the optical fibers delivering the two component beams are polarization maintaining fibers.

15 Optical fiber 102 is disposed in ferrule 104 as is known in the art and is end polished at an angle as is known in the art. Diverging composite optical beam 106 from the end of optical fiber 102 is focussed by lens 108 into Wollaston prism 110, disposed along the optical axis 112 of optical beam 106. Ferrule 104 may have a length of about

4mm, and may be spaced from lens 108 by about 2mm. Lens 108 may be spaced from Wollaston prism 110 by about 2mm.

Wollaston prism 110 separates the composite optical beam 106 into component
5 beams 114 and 116, which leave the Wollaston prism 110 at two different angles
symmetrical about optical axis 112. Lens 118 focuses component optical beams 114 and
116 such that they enter optical fibers 120 and 122, respectively, disposed symmetrically
about optical axis 112 in ferrule 124. As presently preferred, lenses 108 and 118
comprise conventional lenses. Wollaston prism 110 may have a length of about 4mm,
10 and may be spaced from lens 118 by about 2mm. Lens 118 may be spaced from ferrule
124 by about 2mm. Ferrule 124 may have a length of about 4mm.

In the embodiment of FIG. 6, light coming out of the first fiber 102 is not
collimated, but instead the two lenses are used as an imaging system to focus the light
15 into Wollaston prism 110. One advantage of this embodiment is that only one Wollaston
prism 110 is employed. This embodiment, however, requires the imaging lens to be
aberration free, which is difficult to achieve for most common lenses.

As will be appreciated by persons of ordinary skill in the art having the benefit of this disclosure, the present invention provides advantages over prior art splitter/combiners. First, the embodiments of the present invention employ fewer optical parts compared to the prior art arrangements. In addition, the splitter/combiners of the present invention provide improved optical performance including benefits such as lower insertion loss and possibly higher optical polarization extinction ratio by using higher extinction ratio parts. Importantly, the present invention allows manufacture of splitter combiners having much smaller footprints than those of the prior art and permits use of compact coaxial packaging to permit easier fiber management. Because the optical path is epoxy free, higher optical power handling capability is enabled.

Persons of ordinary skill in the art will appreciate that, in embodiments where the optical axis of the input and output fibers are disposed at angles other than 0° and 90° , modified Wollaston prisms fabricated with their optical axes aligned with the optical axes of the input and output fibers will be employed. For example, in an embodiment where the two orthogonal optical axes are disposed at 45° and 135° , the Wollaston prism will have an optical axis disposed at an angle of 45° . This also applies to the walkoff crystals in the other embodiments.

Such skilled persons will also appreciate that the disclosed embodiments of the optical polarized beam combiner/splitter according to the present invention are more compact than those of the prior art. For example, the optical path length of the embodiment of FIG. 3 may be about 18mm. The combined length of the elements in the optical path of the embodiment of FIG. 3 is less than about 32mm. The entire packaged optical polarized beam combiner/splitter according to FIG. 3 of the present invention can fit in a package approximately 20mm long having a diameter of about 5.5mm.

The optical path length of the embodiment of FIG. 4 may be about 33mm. The combined length of the elements in the optical path of the embodiment of FIG. 4 is less than about 32mm. The entire packaged optical polarized beam combiner/splitter according to FIG. 4 of the present invention can fit in a package approximately 36mm long having a diameter of about 5.5mm.

The optical path length of the embodiment of FIG. 5 may be about 27mm. The combined length of the elements in the optical path of the embodiment of FIG. 5 is less than about 26mm. The entire packaged optical polarized beam combiner/splitter

according to FIG. 5 of the present invention can fit in a package approximately 4mm by 30mm having a diameter of about 5.5mm.

The optical path length of the embodiment of FIG. 6 may be about 28mm. The combined length of the elements in the optical path of the embodiment of FIG. 6 is less than 20mm. The entire packaged optical polarized beam combiner/splitter according to FIG. 6 of the present invention can fit in a package approximately 30mm long having a diameter of about 5.5mm.

While embodiments and applications of this invention have been shown and described, it would be apparent to those skilled in the art having the benefit of this disclosure that many more modifications than mentioned above are possible without departing from the inventive concepts herein. The invention, therefore, is not to be restricted except in the spirit of the appended claims.

What is claimed is:

1. An optical polarization beam splitter comprising:
splitter/combiner optical elements aligned along a substantially straight-line
optical path;

5 a first input/output fiber terminating in a first ferrule aligned along a first
end of said optical path;

second and third input/output fibers terminating in a second ferrule aligned
along a second end of said optical path.

10 2. An optical polarization beam splitter comprising:
a first optical fiber having an end defining a first optical axis;
a second optical fiber having an end defining a second optical axis;
a third optical fiber having an end defining a third optical axis parallel to
and spaced apart from said second optical axis;

15 a collimating lens disposed along said first optical axis positioned to form a
collimated optical beam from said first optical fiber;
a focussing lens disposed along a path of said collimated optical beam;

a birefringent walk-off crystal having a first face adjacent to said focussing lens and a second face located at a focal plane of said focussing lens and in contact with said ends of said second and third optical fibers, said crystal oriented such that and having a thickness between said first and second faces selected such that a first component of said optical beam having a first polarization exiting said crystal at said second face enters said end of said second optical fiber along said second optical axis and a second component of said optical beam having a second polarization orthogonal to the polarization of said first polarization exiting said crystal at said second face enters said end of said third optical fiber along said third optical axis.

3. The optical polarization beam splitter of claim 2 wherein said second and third optical fibers are polarization maintaining fibers.

4. The optical polarization beam splitter of claim 2 wherein said second optical axis and said third optical axis are spaced apart by a distance of less than 2mm.

5. The optical polarization beam splitter of claim 2 disposed in a package having a length of less than about 50mm and a diameter of less than about 10mm.

6. The optical polarization beam splitter of claim 2 disposed in a package having a length of no more than about 20mm and a diameter of no more than about 5.5mm.

5
NFCS-99-017
7. An optical polarizing beam splitter comprising:
a first optical fiber having an end defining a first optical axis;
a second optical fiber having an end defining a second optical axis;
a third optical fiber having an end defining a third optical axis parallel to
and spaced apart from said second optical axis;
10 a collimating lens disposed along said first optical axis positioned to form a
collimated optical beam from said first optical fiber;
a birefringent walk-off crystal disposed in a path of said collimated optical
beam, said crystal oriented such that and having a thickness between first and second
faces thereof selected such that a first component of said optical beam having a first
15 polarization transits said crystal along a first path and a second component of said optical
beam having a second polarization orthogonal to that of said first polarization transits
said crystal along a second path disposed at a walkoff angle with respect to said first path

and said first and second paths exit said second face of said crystal as substantially parallel first and second paths;

a Wollaston prism disposed along said substantially parallel first and second paths and oriented such as to bend said substantially parallel first and second paths towards each other to form converging first and second paths;

a focussing lens disposed along said converging first and second paths and positioned such that a first component optical beam travelling along said first converging path is directed into said end of said second optical fiber along said second optical axis and a second component optical beam travelling along said second converging path is directed into said end of said third optical fiber along said third optical axis.

8. The optical polarization beam splitter of claim 7 wherein said second and third optical fibers are polarization maintaining fibers.

9. The optical polarization beam splitter of claim 7 wherein said second optical axis and said third optical axis are spaced apart by a distance of less than 2mm.

10. The optical polarization beam splitter of claim 7 disposed in a package having a length of less than about 50mm and a diameter of less than about 10mm.

11. The optical polarization beam splitter of claim 7 disposed in a package

5 having a length of about 36mm and a diameter of about 5.5mm.

12. An optical polarizing beam splitter comprising:

a first optical fiber having an end defining a first optical axis;

a second optical fiber having an end defining a second optical axis;

10 a third optical fiber having an end defining a third optical axis parallel to and spaced apart from said second optical axis;

a collimating lens disposed along said first optical axis positioned to form a collimated optical beam from said first optical fiber;

a first Wollaston prism disposed in a path of said collimated optical beam

15 and oriented such that a first component of said optical beam having a first polarization transits said prism along a first path disposed at a first angle with respect to said first optical axis and a second component of said optical beam having a second polarization orthogonal to that of said first polarization transits said prism along a second path

disposed at a second angle with respect to said first optical axis, said first and second angles being substantially symmetrical about said first optical axis;

a second Wollaston prism disposed along said first and second paths and oriented such as to bend said first and second paths towards each other to form

5 converging first and second paths;

a focussing lens disposed along said converging first and second paths and positioned such that a first component optical beam travelling along said first converging path is directed into said end of said second optical fiber along said second optical axis and a second component optical beam travelling along said second converging path is
10 directed into said end of said third optical fiber along said third optical axis.

13. The optical polarization beam splitter of claim 12 wherein said second and third optical fibers are polarization maintaining fibers.

15 14. The optical polarization beam splitter of claim 12 wherein said second optical axis and said third optical axis are spaced apart by a distance of less than about 125 microns.

15. The optical polarization beam splitter of claim 12 disposed in a package having a length of less than about 50mm and a diameter of less than about 10mm.

16. The optical polarization beam splitter of claim 12 disposed in a package having a length of no larger than about 30mm and a diameter of no larger than about 5.5mm.

09702280-103000
 10
 17. *Deleted line*

An optical polarizing beam splitter comprising:

- a first optical fiber having an end defining a first optical axis;
- a second optical fiber having an end defining a second optical axis;
- a third optical fiber having an end defining a third optical axis parallel to and spaced apart from said second optical axis, said second and third optical axes being symmetrical about said first optical axis;
- a first focussing lens disposed along said first optical axis;
- a Wollaston prism disposed at a location along said first optical axis where a focal point of said first focussing lens lies on an interface between two component pieces of said prism such that a first component of an optical beam from said first optical fiber having a first polarization is directed along a first path disposed at a first angle with

respect to said first optical axis and a second component of said optical beam having a second polarization orthogonal to that of said first polarization is directed along a second path disposed at a second angle with respect to said first optical axis, said first and second angles being substantially symmetrical about said first optical axis;

5 a second focussing lens disposed along said first and second paths at a location selected to focus a first component optical beam into said end of said second optical fiber to focus a second component optical beam into said end of said third optical fiber.

10 18. The optical polarization beam splitter of claim 17 wherein said second and third optical fibers are polarization maintaining fibers.

15 19. The optical polarization beam splitter of claim 17 wherein said second optical axis and said third optical axis are spaced apart by a distance of less than 2mm.

20. The optical polarization beam splitter of claim 17 disposed in a package having a length of less than about 50mm and a diameter of less than about 10mm.

21. The optical polarization beam splitter of claim 17 disposed in a package having a length of no larger than about 30mm and a diameter of no larger than about 5.5mm.

ABSTRACT OF THE DISCLOSURE

An optical polarization beam splitter comprises a first optical fiber having an end defining a first optical axis, a second optical fiber having an end defining a second optical axis, and a third optical fiber having an end defining a third optical axis parallel to and spaced apart from the second optical axis. A collimating lens is disposed along the first optical axis positioned to form a collimated optical beam from the first optical fiber. A focussing lens is disposed along a path of the collimated optical beam. A birefringent walk-off crystal has a first face adjacent to the focussing lens and a second face located at a focal plane of the focussing lens and in contact with the ends of the second and third optical fibers. The birefringent crystal is oriented such that and has a thickness between its first and second faces selected such that a first component of the optical beam having a first polarization exits the crystal at its second face and enters the end of the second optical fiber along the second optical axis and a second component of the optical beam having a second polarization orthogonal to the polarization of the first polarization exits the crystal at its second face and enters the end of the third optical fiber along the third optical axis.

000007" 000000/00

NFCS-99-001

Optical Polarization Beam Splitter




FIG. 1A

Optical Polarization Beam Combiner




Fig. 1B

Optical Polarization Beam Splitter




Fig. 2A

Optical Polarization Beam Combiner




Fig. 2B




FIG. 3




FIG. 4

70




FIG. 5




FIG. 6

DECLARATION

As a below-named inventor, I hereby declare that:

My correct residence, post office address and citizenship are stated below next to my name.

I believe myself to be the original, first and sole inventor (if only one name is listed below) or an original and first joint inventor (if more than one name is listed below) of the subject matter which is disclosed and claimed and for which a patent is sought on the invention entitled:

"OPTICAL POLARIZATION BEAM COMBINER/SPLITTER"

The specification of this subject matter:

- ☒ is attached hereto.
- ☐ was filed on, 1999;
 was assigned serial No.;
 which was amended on _____.

I hereby state that I have reviewed and understand the contents of the above identified patent application, including the claims, as amended by any amendment(s) referred to above. I believe the subject matter claimed in the above-identified application to be new and to be unobvious to persons of ordinary skill in the art in view of the prior art of which I am aware. I further hereby state that the specification of the above identified patent application adequately describes how to make and use the claimed invention, and further that it sets forth the best mode for practicing the invention known to me as of the date that the application was filed. I acknowledge the duty to disclose information which is material to the examination of this application in accordance with 37 C.F.R. §1.56(a).

I hereby claim foreign priority benefits under 35 U.S.C. §119 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed.

Application No.	Country	Filing Date	Priority Claimed
-----------------	---------	-------------	------------------

I hereby claim the benefit under 35 U.S.C. §120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in these prior United States application(s) in the manner provided by 35 U.S.C. §112, I acknowledge the duty to disclose material information as defined in 37 C.F.R. §1.56(a) which occurred between the filing date of the prior application(s) and the national or PCT international filing date of this application.

Application No.	Filing Date	Status (Issued, Pending, Abandoned)
-----------------	-------------	-------------------------------------

If the rights held by the above identified small business concern are not exclusive, each individual, concern or organization having rights to the invention is listed below and no rights to the invention are held by any person, other than an inventor who qualifies as an individual inventor pursuant to 37 C.F.R. §1.9(c), who could not qualify as a small business concern under 37 CFR 1.9(d) or by any concern which would not qualify as a small business concern under 37 CFR 1.9(d) or a nonprofit organization under 37 CFR 1.9(e).*

*Note: Separate verified statements are required from each named person, concern or organization having rights to the invention averring to their status as small entities. (37 CFR 1.27).

FULL NAME: Yonglin Huang

ADDRESS: 2463 Flickinger Road, San Jose, California 95131

☒ Individual ☐ Small Business Concern ☐ Nonprofit Organization

FULL NAME: Ping Xie

ADDRESS: 1272 Chessington Drive, San Jose, California 95131

☒ Individual ☐ Small Business Concern ☐ Nonprofit Organization

FULL NAME:


ADDRESS:

☐ Individual ☐ Small Business Concern ☐ Nonprofit Organization

I acknowledge the duty to file, in this application or patent, notification of any change in status resulting in loss of entitlement to small entity status prior to paying, or at the time of paying, the earliest of the issue fee or any maintenance fee due after the date on which status as a small business entity is no longer appropriate. (37 CFR 1.28(b)).

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application, any patent issuing thereon, or any patent to which the verified statement is directed.

New Focus, Inc.
2630 Walsh Avenue
Santa Clara, CA 95051


Signature

8/10/99
Date

Timothy Day
Print Name

Chief Technology Officer
Title

COPY

POWER OF ATTORNEY

New Focus Inc., a California corporation, assignee of the application for United States Letters

Patent for an invention entitled:

"OPTICAL POLARIZATION BEAM COMBINER/SPLITTER"

invented by:

Yonglin Huang and Ping Xie

☒ executed on even date herewith, or

☐ having serial No. , filed ,

do(es) hereby appoint Kenneth D'Alessandro, Registration No. 29,144; Sean P. Lewis, Registration No. 42,798; Timothy Brisson, Registration No. 44,064; Michael Brandt, Registration No. 39,119; and Robert Hall, Registration No. 39,209, Jonathan Velasco, Registration No. 42,700, Michael Kerr, Registration No. 42,722, as attorneys of record with full power of substitution and revocation, to prosecute this application and transact all business in the United States Patent and Trademark Office connected therewith, and certifies that it is the assignee of the entire right, title and interest in the patent application identified above by virtue of an assignment, a copy of which is attached, from the inventor(s) of the patent application identified above.

Please send all correspondence and direct all telephone calls to:


Kenneth D'Alessandro
Sierra Patent Group, Ltd.
P.O. Box 6149
Stateline, NV 89449
Telephone (775) 586-9500

The undersigned has reviewed all the documents in the chain of title of the patent application identified above and, to the best of undersigned's knowledge and belief, title is in the assignee identified above.

I, the undersigned, declare that I am the assignee of the above identified application, or, if the assignee is a corporation, partnership, or other association, I am authorized to make this appointment on behalf of the assignee and I further declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application or any patent issuing therefrom.

Full Assignee Name
Post Office Address

New Focus, Inc.
2630 Walsh Avenue, Santa Clara, California 95051-0905


Signature

8/10/99
Date

Timothy Day
Print Name

Chief Technology Officer
Title

CCPY